

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Material number : 00000000001002639

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	liquid
Colour	clear, colourless
Odour	oily

GHS Classification

Flammable liquids : Category 3
 Skin irritation : Category 2
 Serious eye damage : Category 1
 Germ cell mutagenicity : Category 1B
 Carcinogenicity : Category 2
 Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H340 May cause genetic defects.
 H351 Suspected of causing cancer.

Precautionary statements : **Prevention:**

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P264 Wash skin thoroughly after handling.
 P280 Wear protective gloves/ eye protection/ face protection.
 P281 Use personal protective equipment as required.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Potential Health Effects**Carcinogenicity:**

IARC	Group 2B: Possibly carcinogenic to humans	
	ethylbenzene	100-41-4
	naphthalene	91-20-3
	cumene	98-82-8
ACGIH	Confirmed animal carcinogen with unknown relevance to humans	
	ethylbenzene	100-41-4
	cyclohexanone	108-94-1
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.	
NTP	Reasonably anticipated to be a human carcinogen	
	naphthalene	91-20-3

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 70 - < 90
2-ethylhexyl nitrate	27247-96-7	>= 5 - < 10
xylenes	1330-20-7	>= 5 - < 10
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 1 - < 5
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 1 - < 5
ethylbenzene	100-41-4	>= 1 - < 5
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5
cyclohexanone	108-94-1	>= 1 - < 5
naphthalene	91-20-3	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

	Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Standard procedure for chemical fires.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area.
Conditions for safe storage	: Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents Do not freeze.

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylenes	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
ethylbenzene	100-41-4	TWA	100 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
		TWA	25 ppm 125 mg/m3	NIOSH REL
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
cyclohexanone	108-94-1	TWA	20 ppm	ACGIH
		STEL	50 ppm	ACGIH
		TWA	25 ppm 100 mg/m3	NIOSH REL
		TWA	50 ppm 200 mg/m3	OSHA Z-1
		TWA	25 ppm 100 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
naphthalene	91-20-3	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH
cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
-----------	---------	--------------------	---------------------	---------------	---------------------------	-------

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

ETHYLENZENE	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift at end of workweek	700 mg/g	ACGIH BEI
Remarks: Creatinine						
ETHYLENZENE		Ethylbenzene	In end-exhaled air	Not critical		ACGIH BEI
CYCLOHEXANONE	108-94-1	1,2-Cyclohexanediol	Urine	End of shift at end of workweek	80 mg/l	ACGIH BEI
CYCLOHEXANONE		Cyclohexanol	Urine	End of shift (As soon as possible after exposure ceases)	8 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, colourless

Odour : oily

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

Odour Threshold	: no data available
	no data available
pH	: not applicable
Melting point/freezing point	: no data available
Boiling point	: 132 °C
Flash point	: 47.2 °C
	Method: TCC
Evaporation rate	: > 10
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
	no data available
Density	: 0.833 g/cm ³
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: not determined
Partition coefficient: n- octanol/water	: no data available
	no data available
Auto-ignition temperature	: not determined
Thermal decomposition	: no data available
Viscosity	
Viscosity, kinematic	: 6.0 mm ² /s (20.0 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Skin corrosion/irritation**Product:**

Remarks: Irritating to skin.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Distillates (petroleum), hydrotreated light:

2-ethylhexyl nitrate:

xylenes:

Solvent naphtha (petroleum), light arom.:

Solvent naphtha (petroleum), heavy arom.:

ethylbenzene:

1,2,4-trimethylbenzene:

cyclohexanone:

naphthalene:

STOT - single exposure

no data available

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information**Product:**

Remarks: no data available

Remarks: no data available

Remarks: Solvents may degrease the skin.

Components:**Distillates (petroleum), hydrotreated light:**

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

no data available

Persistence and degradability

no data available

Bioaccumulative potential**Product:**Partition coefficient: n-
octanol/water : Remarks: no data available

Remarks: no data available

Components:**xylenes :**Partition coefficient: n-
octanol/water : Pow: 3.12**Solvent naphtha (petroleum), heavy arom. :**Partition coefficient: n-
octanol/water : log Pow: 4.2**ethylbenzene :**Partition coefficient: n-
octanol/water : Pow: 3.6**cyclohexanone :**Partition coefficient: n-
octanol/water : log Pow: 0.81**Mobility in soil**

no data available

Other adverse effects

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

no data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : no data available

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.
no data available

Components:

Distillates (petroleum), hydrotreated light :

Additional ecological information : no data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION
International regulation**IATA-DGR**

UN/ID No. : 1993

Proper shipping name : Flammable liquid, n.o.s.
(HYDROTREATED LIGHT PETROLEUM DISTILLATES)

Class : 3

Packing group : III

Labels : 3

Packing instruction (cargo aircraft) : 366

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

Packing instruction
(passenger aircraft) : 355

IMDG-Code

UN number : 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (HYDROTREATED LIGHT PETROLEUM DISTILLATES)
 Class : 3
 Packing group : III
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : 1993
 Proper shipping name : Flammable liquids, n.o.s.
 (HYDROTREATED LIGHT PETROLEUM DISTILLATES)
 Class : 3
 Packing group : III
 Labels : 3
 ERG Code : 128
 Marine pollutant : no

Special precautions for user

not applicable

SECTION 15. REGULATORY INFORMATION
EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	1346

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
 Acute Health Hazard
 Chronic Health Hazard

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethylbenzene	100-41-4
1,2,4-trimethylbenzene	95-63-6
naphthalene	91-20-3

California Prop 65 WARNING! This product contains a chemical known to the State of California to cause cancer.

ethylbenzene	100-41-4
naphthalene	91-20-3
cumene	98-82-8

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL.
AICS	On the inventory, or in compliance with the inventory
NZIoC	Not in compliance with the inventory
PICCS	On the inventory, or in compliance with the inventory
IECSC	On the inventory, or in compliance with the inventory


Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0

Revision Date 01/09/2015

Print Date 06/23/2015

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause genetic defects. Suspected of causing cancer.

Precautionary statements

:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash skin thoroughly after handling. Wear protective gloves/eye protection/face protection. Use personal protective equipment as required.

Response: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.