



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Liquid Caustic Soda, 25%
PRODUCT ID: 0158
SYNONYMS: Liquid Caustic Soda; Sodium Hydroxide; NaOH
ISSUE DATE: 11/06/2000
EDITION NO.: 10

PPG Industries, Inc.
One PPG Place, Pittsburgh, PA 15272, USA
24-hour Emergency Telephone Number: 1-304-843-1300
For Product Information (8am-5pm Eastern time):
1-800-243-6774 (C/A)

PREPARER: Product Safety, Chemicals

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Material/CAS Number</u>	<u>Percent</u>
Water 7732-18-5	75
Sodium Hydroxide 1310-73-2	25

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

DANGER! Corrosive - Causes severe burns to eyes and skin.

Precautions: Do not get in eyes, on skin, or on clothing. Corrosive to skin. Even a small amount in the eye can cause blindness. Do not swallow. Avoid breathing dusts or mists from solutions. Use only with adequate ventilation. Ventilation must be sufficient to limit employee exposure to this product below permissible exposure limits. When making solutions or diluting, only add caustic soda slowly to surface of cold water while stirring. Do not add to warm or hot water, a violent eruption or explosive reaction can result. Avoid contact with organic materials and concentrated acids - may cause violent reactions. Caustic soda reacts with magnesium, aluminum, zinc (galvanized), tin, chromium, brass and bronze, generating hydrogen which is explosive. Caustic soda may react with various sugars to generate carbon monoxide. Hazardous carbon monoxide gas can form upon contact with food and beverage products in enclosed vessels and can cause death. Wash thoroughly after handling. Do not eat, drink or smoke in work area. Liquid caustic soda is shipped hot (100-180

PPG: 0158 Liquid Caustic Soda, 25% 11/06/2000

F). Avoid skin contact -- can cause thermal burns.

4. FIRST AID MEASURES

INHALATION: Move person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult. If breathing is difficult, give oxygen. Call a physician.

EYE/SKIN CONTACT: In case of contact, immediately flush eyes and skin with plenty of water (soap and water for skin) for at least 15 minutes, while removing contaminated clothing and shoes. Hold eyelids open during this flushing with water. Call a physician. If skin feels slippery, this product may still be present in sufficient quantities to cause rash or burn. Continue washing until slick skin feeling is gone. Thoroughly clean contaminated clothing and shoes before reuse or discard.

INGESTION: If swallowed, give at least 3-4 glasses of water or acidic beverages (tomato or orange juice, carbonated soft drinks). Do not induce vomiting. Do not give anything by mouth to an unconscious or convulsing person. Get medical attention.

NOTES TO PHYSICIAN:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLASH POINT: None

EXTINGUISHING MEDIA: Not applicable.

SPECIAL FIREFIGHTING PROCEDURES: Contact with some metals (particularly magnesium, aluminum and galvanized zinc) can rapidly generate hydrogen, which is explosive.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Only trained personnel equipped with NIOSH approved, full facepiece combination dust/mist respirators should be permitted in area. For dry material, use appropriate methods, shovels, brooms, and vacuums to clean up the spill. If mixed with water, or likely to become mixed with water or any liquid, dike area to contain spill. Reclaim if possible. Or, dilute spill with large amounts of water then neutralize with dilute acid. Use vacuum truck to pick up neutralized material for proper disposal. Properly neutralized liquid residues (pH 6 to 9) may be disposed of in waste water treatment facilities which allow the discharge of neutral salt solutions. After all visible traces have been removed, flush area with large amounts of water.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:

Wear appropriate personal protective equipment. Never touch eyes or face with hands or gloves that may be contaminated with this product. When making solutions or diluting, only add caustic soda slowly to surface of cold water while stirring. Do not add to warm or hot water, a violent eruption or

PPG: 0158 Liquid Caustic Soda, 25% 11/06/2000

explosive reaction can result. Avoid contact with organic materials and concentrated acids - may cause violent reactions. Caustic soda reacts with magnesium, aluminum, zinc (galvanized), tin, chromium, brass and bronze, generating hydrogen which is explosive. Caustic soda may react with various sugars to generate carbon monoxide. Hazardous carbon monoxide gas can form upon contact with food and beverage products in enclosed vessels and can cause death. Follow appropriate tank entry procedures (see ANSI Z177.1 - 1977). Do not enter a storage tank or container (truck or rail) that has contained this product, even if it appears empty. Liquid caustic soda is shipped hot (100-180 °F). Avoid skin contact -- can cause thermal burns.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

8-hour Time Weighted Average (TWA); 15-minute Short-Term Exposure Limit (STEL)

OSHA: 2 mg/cu.m. Ceiling. 29 CFR 1910.1000 (Rev. 3/1/89).

RESPIRATORY PROTECTION: Use a NIOSH approved dust/mist filter respirator for all routine activities when exposure to dusts/mists exceed the permissible exposure limits. The respiratory use limitations made by NIOSH or the manufacturer must be observed. Respiratory protection programs must be in accordance with 29 CFR 1910.134.

VENTILATION: Use local exhaust sufficient to maintain dust/mist levels below permissible exposure limits.

EYE AND FACE PROTECTION: Close fitting chemical safety goggles with faceshield.

PROTECTIVE GLOVES: Nitrile. Neoprene. Natural rubber.

OTHER PROTECTIVE EQUIPMENT: Rubber boots with safety toes, rubber aprons, PVC clothing, and plastic hard hats should be used when necessary to prevent skin contact. Personal protective clothing and use of equipment must be in accordance with 29 CFR 1910.132 (general requirements), .133 (eye and face protection), and .138 (hand protection).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:	233 °F
VAPOR DENSITY (Air=1):	NA
SPECIFIC GRAVITY (Water=1):	1.219 @ 68/68 °F
pH:	Strongly basic
FREEZING/MELTING POINT:	4 °F
SOLUBILITY (wt.% in water):	Complete
BULK DENSITY:	10.16 lbs/gal @ 68 °F
VOLUME % VOLATILE:	75
VAPOR PRESSURE:	1 mm Hg
EVAPORATION RATE:	NA
HEAT OF SOLUTION:	Exothermic
PHYSICAL STATE:	Liquid

PPG: 0158 Liquid Caustic Soda, 25%	11/06/2000
------------------------------------	------------

ODOR: Odorless
 COLOR: Water white to slightly turbid

10. STABILITY AND REACTIVITY

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY (CONDITIONS/MATERIALS TO AVOID):

Contact with organic materials and concentrated acids may cause violent reactions. Contact with magnesium, aluminum, galvanized zinc, tin, chromium, brass and bronze generates explosive hydrogen. Reactions with various food sugars may form carbon monoxide.

HAZARDOUS THERMAL DECOMPOSITION/COMBUSTION PRODUCTS:

Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

ACUTE INHALATION LC50: Corrosive
 SKIN IRRITATION: Corrosive.
 EYE IRRITATION: Corrosive.
 ACUTE ORAL LD50: LDLo (rabbit) 500 mg/kg. Corrosive.

CHRONIC EFFECTS/CARCINOGENICITY: This product is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

MEDICAL CONDITIONS AGGRAVATED: None known.

EFFECTS OF OVEREXPOSURE:

ACUTE:

Eye/Skin: Causes severe burns to the eyes. Small quantities can result in permanent damage and/or loss of vision. For skin contact, corrosive action causes burns and frequently deep ulcerations with subsequent scarring. Prolonged contact destroys tissue. Dust or mist from solutions can cause irritant dermatitis.

Ingestion: Ingestion either in solid or liquid form can cause very serious damage to the mucous membranes or other tissues with which contact is made, and may be fatal.

Inhalation: Inhalation of dusts or mists can cause damage to the upper respiratory tract and to the lung tissue depending on severity of exposure. Effects can range from mild irritation of mucous membranes, severe pneumonitis and destruction of lung tissues.

CHRONIC: The effects of long-term, low level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the prevention of all contact

PPG: 0158 Liquid Caustic Soda, 25% 11/06/2000

with this material to avoid any effects from repetitive acute exposures.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:

Highly toxic to aquatic life. 240 ug/l (Bluegill) 96-hour TLM LC50

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD:

PPG recommends disposal of dry residues in an approved hazardous waste management facility or by neutralizing and disposing of according to local or permitted regulations. Care must be taken when using or disposing of chemical materials and/or their containers to prevent environmental contamination. It is your duty to dispose of the chemical materials and/or their containers in accordance with the Clean Air Act, the Clean Water Act, the Resource Conservation and Recovery Act, as well as any other relevant Federal, State, or local laws/regulations regarding disposal.

14. TRANSPORT INFORMATION

USA DOT DESCRIPTION:

Proper Shipping Name: Sodium Hydroxide, Solution
 Hazard Class: 8 (Corrosive)
 Identification Number: UN1824
 Packing Group: II
 Reportable Quantity: 1000 lbs./454 kg

15. REGULATORY INFORMATION

USA TSCA: This product is listed on the TSCA Inventory.
 EUROPE EINECS: This product is listed on EINECS.
 CANADA DSL: This product is listed on the Canadian DSL.
 AUSTRALIA AICS: This product is listed on AICS.
 KOREA ECL: This product is listed on ECL.
 JAPAN MITI (ENCS): This product is listed on MITI.

SARA TITLE III:

SARA (311, 312) Hazard Class:
 Acute Health Hazard. Reactive Hazard.

SARA (313) Chemicals:

Not listed.

SARA Section 302:

Not listed as an Extremely Hazardous Substance.

CERCLA HAZARDOUS SUBSTANCE:

Listed in Table 302.4 of 40 CFR Part 302 as a hazardous substance with a reportable quantity of 1000 pounds. Releases to air, land or water which exceed the RQ must be reported to the National Response Center, 800-424-8802.

PPG: 0158 Liquid Caustic Soda, 25% 11/06/2000

HAZARD RATING SYSTEM (HMIS/NFPA):

Health 3, Flammability 0, Reactivity 1

16. OTHER INFORMATION

Other Information:

In case of emergency in Canada, contact PPG Canada, Inc., B.P. 2010, Beauharnois, Quebec J6N 3C3, 450-429-3552, or Canutec 613-996-6666.

The following has been revised since the last issue of this MSDS:

Date. Edition. Section 2 has been updated. Section 15 has been updated. Section 16 has been updated.

Previous revision date: 10/15/1997
Previous edition number: 009

NA = Not Available